

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 September 2004 (02.09.2004)

PCT

(10) International Publication Number
WO 2004/073533 A1

(51) International Patent Classification⁷: **A61B 17/70**

(21) International Application Number:
PCT/IB2004/000390

(22) International Filing Date: 17 February 2004 (17.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03/02038 19 February 2003 (19.02.2003) FR

(71) Applicant (for all designated States except US): **SDGI HOLDINGS INC.** [US/US]; 300 Delaware Avenue, Suite 508, Wilmington State Of Delaware, Delaware 19801 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MAXY, Philippe** [FR/FR]; 5, Ruelle Beaubourg, Claye Souilly 77410 (FR). **GOURNAY, José** [FR/FR]; 36, Avenue Du Drap D'or, Dammartin En Goele 77230 (FR).

(74) Agents: **NEYRET, Daniel** et al.; Cabinet Lavoix, 2, Place d'Estienne d'Orves, F-75441 Paris Cedex 09 (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **INTERSPINOUS DEVICE FOR IMPEDING THE MOVEMENTS OF TWO SUCCESSIVE VERTEBRAE, AND METHOD FOR MAKING A PAD DESIGNED FOR IT**



(57) Abstract: Interspinous device for impeding the movements of two successive vertebrae (8, 9) of the spinal column, characterized in that it comprises: - two pads (2a, 2b; 11a, 11b; 20a, 20b) whose internal faces (3a, 3b; 12a, 12b) are intended to be pressed against the lateral faces of the spinous processes (6, 7) of the said vertebrae (8, 9), - and ligaments (4, 5a, 5b, 5c, 5d; 17a, 17b, 18, 19; 23, 24) which connect the said pads (2a, 2b; 11a, 11b; 20a, 20b) to each other and to the said spinous processes (6, 7), so that, during flexion and extension movements of the spinal column with respect to its normal position, the pressures exerted against the lateral faces of the spinous processes (6, 7) by the said pads (2a, 2b; 11a, 11b; 20a, 20b) increase as the spinal column moves away from the said normal position. Method for making a pad designed for such a device.

**Interspinous device for impeding the movements
of two successive vertebrae, and method for making a
pad designed for it**

The invention relates to the field of surgical implants
5 intended to impede the coming-together of two vertebrae
during movements of the spinal column.

When intervertebral discs have been subject to
considerable wear or degeneration, they may become
10 powerless to prevent excessive coming-together of two
successive vertebrae during flexion (forward movement)
or extension (backward movement) of the spinal column.
Such coming-together may have the consequence of
crushing the spinal nerves, which is very painful for
15 the patient. In the most serious cases, this coming-
together may continue until the vertebrae contact one
another during extreme movements.

A first known method for solving this problem consists
20 in fastening one of the vertebrae in question to the
other, so as to keep a space between them which is
permanently enough. This fastening may be carried out
by means of various devices in the form of plates.
However, it causes a significant loss of mobility for
25 the patient, because it prohibits any flexion or
extension of the spinal column in the region in
question.

It is also known to ligature the spinous processes of
30 the vertebrae in question by means of artificial
ligaments. This makes it possible to retain freedom of
movement in extension for the vertebrae while limiting
the magnitude of the allowed flexions, to the extent of
prohibiting contact between the front of the vertebrae.
35 However, this does not prevent contact at the back of
the vertebrae, although this region is where
compression of the spinal nerves is most likely to
occur.

It is also known to insert interspinous wedges between the spinous processes, as in document EP-A-0 392 124. These wedges are made of a rigid material such as PTFE, and thus prevent any contact between the spinous
5 processes that they separate during extension of the spinal column. Preferably, they are held in place by artificial ligaments which pass through them and are wound around the spinous processes. By virtue of these ligaments, it is also possible to limit the magnitude
10 of flexion movements of the spinal column in the region in question.

However, the fact of having a rigid element between the spinous processes leads to virtual removal of the
15 extension movements of the spinal column at that point, or at least to a sudden interruption of such movements when the processes come into contact with the wedge.

It would be desirable to be able to use a device
20 reproducing the normal behaviour of a vertebra-disc-vertebra stack (functional unit) more faithfully, where normally the action of blocking the movements of the spinal column only takes place gradually.

25 The aim of the invention is to provide a device meeting this requirement.

To this end, the subject of the invention is an interspinous device for impeding the movements of two
30 successive vertebrae of the spinal column, characterized in that it comprises:

- two pads whose internal faces are intended to be pressed against the lateral faces of the spinous processes of the said vertebrae,
- 35 - and ligaments which connect the said pads to each other and to the said spinous processes, so that, during flexion and extension movements of the spinal column from its normal position, the pressures exerted against the lateral faces of the spinous processes by

the said pads increase as the spinal column moves away from the said normal position.

Each of the said pads may have a protuberance intended
5 to penetrate into the interspinous space.

Each of the said pads may consist of a tape folded over and sewn onto itself.

10 Each of the said pads may consist of a solid object.

The device may comprise a pin passing through transverse perforations in the said pads intended to be placed facing the interspinous space separating the two
15 vertebrae, the said pin having flanges able to bear against the surfaces of the said pads, surfaces turned outwards from the spinal column.

The said ligaments may comprise:

- 20 - one ligament in the form of a tape fitting tightly around the pads and having free parts which, when tensioned, make a space having a width "d" greater than a distance separating the interspinous processes of the vertebrae,
- 25 - and four ligaments which are each attached to an upper part or to a lower part of a pad.

Each of the said pads may comprise:

- 30 - one longitudinal perforation connecting the upper part and the lower part of the pad,
 - and two upper and lower transverse perforations connecting the internal face and the external face of the pad,
- and the device may comprise two ligaments which are
35 each inserted in one of the said longitudinal perforations, one ligament which is inserted in the upper transverse perforations of the said pads and one ligament which is inserted in the lower transverse perforations of the said pads.

In each pad, the said transverse perforations can then intersect the said longitudinal perforation, the ligaments inserted in the longitudinal perforations are
5 in the form of a tape and the said ligaments inserted in the transverse perforations pass through the ligaments inserted in the longitudinal perforations.

Each pad may have a longitudinal perforation connecting
10 the upper part and the lower part of the pad and a ligament inserted in the said longitudinal perforation, one end of which is free and the other end of which is shaped in a loop so that it can be ligatured with the free end of the ligament inserted in the longitudinal
15 perforation of the other pad.

The subject of the invention is also a method for making a pad for such an interspinous device, characterized in that said pad is made by folding back
20 and sewing on itself a tape made of a material such as polyester or an elastomer.

As will be understood, the invention consists in providing an interspinous device whose main elements
25 consist of two elements pressed against the lateral faces of the spinous processes. They are made from a relatively flexible material having properties of compressibility and low elasticity. Polyesters and elastomers, or even some composites, may be used for
30 this purpose. They may have a shape such that they slightly penetrate into the interspinous space at rest. They are held against the processes by artificial ligaments and are connected to each other in order to form an assembly:

- 35 - either by the same ligaments which hold them in place against the spinous processes;
- or by an envelope which confines them both at some distance from each other and on which the processes rest when the device is in place;

- or by a centring pin passing through both pads and passing through the interspinous space;
- or by several of these devices at the same time.

5 The elements are pressed against the spinous processes such that they transmit lateral pressures to them equally well during flexion movements as during extension movements of the spinal column, and also during rotational movements. These pressures increase
10 as the spinal column moves away from its normal position, and end up being sufficiently high to stop the possibility of movement before excessive coming-together of the vertebrae takes place.

15 The invention will be better described with the help of the following appended figures:

- Figures 1a, 1b which show a first embodiment of the invention, in the rest state (Figure 1a) and when placed between two vertebrae (Figure 1b);
- 20 - Figures 2a, 2b which show a second embodiment of the invention in the rest state, seen from the front in longitudinal section (Figure 2a) and in profile (Figure 2b);
- Figures 3a and 3b which show, seen in longitudinal
25 section, the second embodiment of the invention at two stages of its placement;
- Figure 4 which shows, seen in longitudinal section, a third embodiment of the invention after its placement.

30

A first embodiment of the invention is shown in Figures 1a and 1b. In the rest state (Figure 1a), the interspinous device 1 is in the form of two pads 2a, 2b, each one having an internal face in the form of a
35 substantially flat surface 3a, 3b intended to rest against the vertebrae when the wedge is put in place. In the example shown, each of these pads 2a, 2b is formed by a tape made of a material having some compressibility and low elasticity, such as polyester

or an elastomer, folded over and sewn onto itself in order to form a stack of a general external shape that is, for example, hemispherical, semi-ovoid, or similar. The pads 2a, 2b fit tightly within the same tape-type
5 ligament 4 made of a material comparable to that of the pads 2a, 2b, and the free parts of which connect, on the one hand, the upper parts and, on the other hand, the lower parts of the pads 3a, 3b, and which leaves the flat surfaces 3a, 3b free. This tape 4 itself bears
10 four ligaments 5a, 5b, 5c, 5d which are attached to it in the respective vicinities of the upper and lower parts of the pads 2a, 2b. The tape 4 is fastened to the pads 2a, 2b and, in the rest state, when tensioned, its free parts allow a space of width "d" to be made
15 between the internal surfaces 3a, 3b of the pads 2a, 2b.

When the interspinous device 1 is put in place on the spinous processes 6, 7 of two successive upper 8 and
20 lower 9 vertebrae, it is as shown in Figure 1b. The device 1 is inserted between the spinous processes 6, 7 which are separated heightwise by a length substantially less than "d". In this way, the lower part of the spinous apophysis 6 of the upper vertebra 8
25 and the upper part of the spinous apophysis 7 of the lower vertebra 9 tension the tape 4. This tension compresses and brings together the pads 2a, 2b, the flat internal surfaces 3a, 3b of which come into contact with the sides of the spinous processes 6, 7
30 and exert pressure forces on them in the direction of the arrows 10, 10', 10'', 10'''. The placement of the device 1 is completed by ligaturing ligaments 5a, 5b at the upper part of the spinous apophysis 6 of the upper vertebra 8 and ligaments 5c, 5d at the lower part of
35 the spinous apophysis 7 of the lower vertebra 9.

In this way, when the spinal column operates in extension, that is to say when the patient bends backwards, and when the spinous processes 6, 7 tend to

come close to each other, the tension exerted on the tape 4 at its free parts tends to increase. The effect of this is to gradually increase the compression of the pads 2a, 2b (especially at their ends) and the pressures exerted by them on the spinous processes 6, 7 in the direction of the arrows 10, 10', 10'', 10'''. The dimensional and mechanical characteristics of the various elements of the device 1 are calculated so that the pressures exerted by the pads 2a, 2b on the spinous processes 6, 7 end up becoming enough to stop the coming-together thereof before causing trauma to the spinal nerves passing between the processes 6, 7, as would occur with a healthy functional unit.

On the other hand, when the spinal column operates in flexion, that is to say when the patient bends forwards, and when the spinous processes 6, 7 tend to move away from each other, this has the effect of increasing the tension exerted on the ligaments 5a, 5b, 5c, 5d. This increased tension is transmitted to the tape 4, at its parts which are fastened to the pads 2a, 2b. This has the effect, as in the previous case, of gradually increasing the compression of the pads 2a, 2b and the pressures exerted by them on the spinous processes 6, 7 in the direction of the arrows 10, 10', 10'', 10'''. It is necessary that, beyond a certain separation of the spinous processes 6, 7, these pressures become great enough to prevent any further separation which would risk causing trauma, as would occur with a healthy functional unit. The ligaments 5a, 5b, 5c, 5d also play a role in impeding and interrupting the flexion movements of the spinal column, because of their possibilities of limited extension.

35

As a variant, each of the pads 2a, 2b may be made in the form of a solid object, for example made of silicon lined with polyester, whose faces turned towards the spinous processes 6, 7 may be flat (as in the previous

example) or may each have a protuberance slightly penetrating into the inter-apophysis space so that the coming-together movements of the spinous processes 6, 7 can be blocked more efficiently and reliably.

5

The variant of the invention shown in Figures 2a, 2b, 3a, 3b has such pads 11a, 11b, made in the form of solid objects of approximately hemispherical or semi-ovoid shape. In the example shown, each of the pads
10 11a, 11b have their face 12a, 12b intended to be turned towards the spinous processes 6, 7 which is of flat shape, it being understood that the said faces 12a, 12b could each have a protuberance as described above.

15 Each of the pads 11a, 11b has a series of perforations intended to allow the passage of the various ligaments making it possible to attach the pads 11a, 11b to the spinous processes 6, 7:

- one longitudinal perforation 13a, 13b which, in
20 the example shown, lies substantially parallel to the periphery of the face 14a, 14b of the pad 11a, 11b intended to be turned away from the spinous processes 6, 7, and connects the upper region to the lower region of the pad 11a, 11b;

25 - and two transverse perforations 15a, 15b; 16a, 16b, one 15a, 15b located in the upper part of the pad 11a, 11b and the other 16a, 16b located in the lower part of the pad 11a, 11b, which connect the internal faces 12a, 12b and external faces 14a, 14b of the pad
30 11a, 11b.

In the example shown, the transverse perforations 15a, 15b; 16a, 16b pass through the longitudinal perforations 13a, 13b; however, this configuration is
35 not essential.

Ligaments pass through the various perforations as follows:

- each of the tape-type ligaments 17a, 17b passes through the longitudinal perforation 13a, 13b of one of the pads 11a, 11b;
- one and the same wire-type upper ligament 18
5 passes through the upper transverse perforation 15a, 15b of each of the pads 11a, 11b;
- and one and the same wire-type lower ligament 19 passes through the lower transverse perforation 16a, 16b of each of the pads 11a, 11b.

10

In the example shown, each wire ligament 18, 19 passes through the tape-type links 17a, 17b, but it must be understood that this arrangement is not essential, in particular if the transverse perforations (15a, 15b;
15 16a, 16b) do not pass through the longitudinal perforations 13a, 13b.

The interspinous device provided by the pads 11a, 11b is implanted, as shown in Figures 3a, 3b.

20

First of all, the pads 11a, 11b are placed against the spinous processes 6, 7 of two successive vertebrae, with the upper wire ligament 18 passing under the apophysis 6 of the upper vertebra, and the lower wire
25 ligament 19 passing over the apophysis 7 of the lower vertebra. The wire ligaments 18, 19 are then ligatured around their respective processes 6, 7, as shown in Figure 3a.

30 Secondly, the tape-type ligaments 17a, 17b are tied or fastened to each other at their two ends, as shown in Figure 3b. This operation finishes putting the pads 11a, 11b in compression against the processes 6, 7, and makes it possible for them to function in a manner
35 comparable to that of the device 1 shown in Figures 1a, 1b during flexions and extensions of the spinal column.

Compared to the variant previously described and shown in Figures 1a, 1b, this variant has the advantage of

not needing the interspinous ligaments to be sectioned for its implantation. The stability of the region concerned of the spinal column is thus improved.

5 Instead of consisting of solid objects as shown, the pads 11a, 11b could consist of tapes folded back on themselves, like the pads 2a, 2b. Under these conditions, the tape-type ligaments 17a, 17b may simply be fastened to the external faces 14a, 14b of the pads
10 11a, 11b without being housed in longitudinal perforations 13a, 13b in pads 11a, 11b. Moreover, this configuration could also be adopted with solid pads 11a, 11b.

15 Another variant of the invention is shown in Figure 4. In this variant, the interspinous device consists of two pads 20a, 20b, each one of which has a protuberance 21a, 21b able to penetrate into the inter-apophysis space (as has been mentioned, such protuberances may be
20 present on the pads of the other variants which have been described). These pads 20a, 20b have longitudinal perforations 22a, 22b comparable to the longitudinal perforations 13a, 13b of the previous variant. Each of the latter encloses a wire- or tape-type ligament 23,
25 24, one end 25, 26 of which is shaped into a loop. The ligaments 23, 24 are inserted into the pads 20a, 20b so that one 25 of the loops is placed on the lower face of its pad 20a, and the other 26 on the upper face of its pad 20b. When the interspinous device is put in place,
30 the free end of each ligament 23, 24 is ligatured in the loop 25, 26 of the other ligament 24, 23.

In this way, when the spinal column operates in flexion, the forces exerted by the processes 6, 7 on
35 the ligaments 23, 24 tension the latter and they tend to press the pads 20a, 20b against the processes 6, 7, the movements of which are impeded as in the previous variants. When the spinal column operates in extension, the pads 20a, 20b tend to separate from each other

under the effect of the forces exerted by the processes 6, 7 on the protuberances 21a, 21b; however, this separation is impeded by the forces exerted on the ligaments 23, 24. The latter transmit these forces to
5 the extreme parts of the pads 20a, 20b, which tend to be pressed against the processes 6, 7 and therefore impede their coming together. Effects similar to those which have been described for the previous variants thus occur again.

10

In the example shown in Figure 4, the interspinous device has another feature which is only optional and which may, likewise, be transposed to the other variants of the invention. Each pad 20a, 20b has a
15 transverse perforation 27, 28 placed substantially in the central region of the pad 20a, 20b. The perforations are intended to face the interspinous space after the device has been put in place and to face each other. A pin 29 made of a rigid or slightly
20 deformable material, fitted at its ends with flanges 30, 31, each one bearing against the surface of a pad 20a, 20b turned outwards from the spinal column, passes through these transverse perforations 27, 28. This pin 29 is inserted into the pads 20a, 20b before or after
25 the interspinous device has been put in place. The prime function of this pin 29 is to provide proper centring of the pads 20a, 20b with respect to one another. It also makes it possible to prevent a lateral expansion of the pads 20a, 20b during the extension
30 movements of the spinal column. The stresses to which the pads 20a, 20b are subject are then transferred to their ends, and this increases the pressure forces exerted on the processes 6, 7.

35 As a variant, the pin 29 may consist of a protuberance from one of the pads 20a, 20b, penetrating into a transverse perforation of the other pad where it is held by a flange secured to the pin after its insertion into the other pad.

It must be understood that the examples which have been described and shown are not limiting, and that, in particular, it would be possible to transpose to some
5 other variants elements which have only been described for a single one of them if there is no obvious incompatibility which would prevent it.

CLAIMS

1. Interspinous device for impeding the movements of two successive vertebrae (8, 9) of the spinal column, characterized in that it comprises:
- 5 - two pads (2a, 2b; 11a, 11b; 20a, 20b) whose internal faces (3a, 3b; 12a, 12b) are intended to be pressed against the lateral faces of the spinous processes (6, 7) of the said vertebrae (8, 9),
- 10 - and ligaments (4, 5a, 5b, 5c, 5d; 17a, 17b, 18, 19; 23, 24) which connect the said pads (2a, 2b; 11a, 11b; 20a, 20b) to each other and to the said spinous processes (6, 7), so that, during flexion and extension movements of the spinal column from its normal position, the pressures exerted against the lateral
- 15 faces of the spinous processes (6, 7) by the said pads (2a, 2b; 11a, 11b; 20a, 20b) increase as the spinal column moves away from the said normal position.
- 20 2. Device according to Claim 1, characterized in that each of the said pads has a protuberance (21a, 21b) intended to penetrate into the interspinous space.
3. Device according to Claim 1 or 2, characterized in that each of the said pads (2a, 2b) consists of a tape
- 25 folded over and sewn onto itself.
4. Device according to Claim 1 or 2, characterized in that each of the said pads (11a, 11b; 20a, 20b)
- 30 consists of a solid object.
5. Device according to one of Claims 1 to 4, characterized in that it comprises a pin (29) passing through transverse perforations (27, 28) in the said
- 35 pads (20a, 20b) intended to be placed facing the interspinous space separating the two vertebrae (8, 9), the said pin (29) having flanges (30, 31) able to bear against the surfaces of the said pads (20a, 20b), surfaces turned outwards from the spinal column.

6. Device according to one of Claims 1 to 5, characterized in that the said ligaments comprise:

- one ligament (4) in the form of a tape fitting tightly around the pads (2a, 2b) and having free parts which, when tensioned, make a space having a width "d" greater than a distance separating the interspinous processes (6, 7) of the vertebrae (8, 9),
- and four ligaments (5a, 5b, 5c, 5d) which are each attached to an upper part or to a lower part of a pad (2a, 2b).

7. Device according to one of Claims 1 to 5, characterized in that the said pads (11a, 11b) each comprise:

- one longitudinal perforation (13a, 13b) connecting the upper part and the lower part of the pad (11a, 11b),
 - and two upper (15a, 15b) and lower (16a, 16b) transverse perforations connecting the internal face and the external face of the pad (11a, 11b),
- and in that it comprises two ligaments (17a, 17b) which are each inserted in one of the said longitudinal perforations (13a, 13b), one ligament (18) which is inserted in the upper transverse perforations (15a, 15b) of the said pads (11a, 11b) and one ligament (19) which is inserted in the lower transverse perforations (16a, 16b) of the said pads (11a, 11b).

8. Device according to Claim 7, characterized in that, in each pad (11a, 11b), the said transverse perforations (15a, 15b; 16a, 16b) intersect the said longitudinal perforation (13a, 13b), in that the ligaments (17a, 17b) inserted in the longitudinal perforations (13a, 13b) are in the form of a tape and in that the said ligaments (18, 19) inserted in the transverse perforations (15a, 15b; 16a, 16b) pass through the ligaments (13a, 13b) inserted in the longitudinal perforations (13a, 13b).

9. Device according to one of Claims 1 to 5,
characterized in that each pad (20a, 20b) has a
longitudinal perforation (22a, 22b) connecting the
5 upper part and the lower part of the pad (20a, 20b) and
a ligament (23, 24) inserted in the said longitudinal
perforation (22a, 22b), one end of which is free and
the other end (25, 26) of which is shaped in a loop so
that it can be ligatured with the free end of the
10 ligament (23, 24) inserted in the longitudinal
perforation (22a, 22b) of the other pad (20b, 20a).

10. Method for making a pad for an interspinous device
according to claim 3 or 6, characterized in that said
15 pad is made by folding back and sewing on itself a tape
made of a material such as polyester or an elastomer.

1/2




FIG. 1a




FIG. 1b




FIG. 2a




FIG. 2b

2/2




FIG. 3a




FIG. 3b




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/000390

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A61B17/70		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) IPC 7 A61B A61F		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 775 183 A (TAYLOR JEAN) 27 August 1999 (1999-08-27) abstract; claim 1; figures 1,5 page 2, line 3-8	1,2,4
X	FR 2 818 530 A (SPINE NEXT) 28 June 2002 (2002-06-28) abstract; claim 1; figure 1	1,2,4
P,X	WO 03/015645 A (LECHMANN BEAT ;MATHIEU CLAUDE (CH); SYNTHES AG (CH); PAVLOV PAUL () 27 February 2003 (2003-02-27) abstract; claim 1; figures 2,3	1,2,4,5
E	FR 2 844 179 A (TAYLOR JEAN) 12 March 2004 (2004-03-12) abstract; claim 1; figure 1	1,2
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C.		<input checked="" type="checkbox"/> Patent family members are listed in annex.
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 26 May 2004		Date of mailing of the international search report 04/06/2004
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Macaire, S

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/000390

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2001/016743 A1 (ZUCHERMAN JAMES F ET AL) 23 August 2001 (2001-08-23) abstract; figures 18-22,34 paragraphs '0064!-'0068!', '0078! -----	1-3, 10
A	US 5 496 318 A (HOWLAND ROBERT S ET AL) 5 March 1996 (1996-03-05) abstract; figure 6 -----	1,2,4,5

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB2004/000390

Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-9

Interspinous device comprising two pads that could consist of a tape folded over and sewed onto itself or could consist of solid objects.

2. Claim : 10

Method of making a pad made by folding back and sewing a tape made of material such as a polyester or an elastomer.

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No
PCT/IB2004/000390

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2775183	A	27-08-1999	FR 2775183 A1	27-08-1999
			DE 69913659 D1	29-01-2004
			EP 1056408 A1	06-12-2000
			WO 9942051 A1	26-08-1999
			US 6626944 B1	30-09-2003
FR 2818530	A	28-06-2002	FR 2818530 A1	28-06-2002
			EP 1343424 A1	17-09-2003
			WO 02051326 A1	04-07-2002
			TW 520986 B	21-02-2003
			US 2004024458 A1	05-02-2004
WO 03015645	A	27-02-2003	WO 03015645 A1	27-02-2003
			EP 1418852 A1	19-05-2004
			TW 534811 B	01-06-2003
FR 2844179	A	12-03-2004	FR 2844179 A1	12-03-2004
			WO 2004024010 A1	25-03-2004
US 2001016743	A1	23-08-2001	US 6419676 B1	16-07-2002
			US 6379355 B1	30-04-2002
			US 6090112 A	18-07-2000
			US 5836948 A	17-11-1998
			US 6451020 B1	17-09-2002
			US 2001020170 A1	06-09-2001
			US 6156038 A	05-12-2000
			AU 741210 B2	22-11-2001
			AU 5903498 A	31-07-1998
			CA 2288252 A1	09-07-1998
			CN 1246041 A	01-03-2000
			EP 0959792 A1	01-12-1999
			JP 2001507599 T	12-06-2001
			WO 0191658 A1	06-12-2001
			WO 0207623 A1	31-01-2002
			US 6074390 A	13-06-2000
			WO 9829047 A1	09-07-1998
			US 5876404 A	02-03-1999
			US 6068630 A	30-05-2000
			US 6048342 A	11-04-2000
			US 6183471 B1	06-02-2001
			US 6149652 A	21-11-2000
			US 6152926 A	28-11-2000
			US 2001016776 A1	23-08-2001
			US 6235030 B1	22-05-2001
			US 6238397 B1	29-05-2001
			US 6190387 B1	20-02-2001
			US 6332882 B1	25-12-2001
			US 6280444 B1	28-08-2001
			US 6332883 B1	25-12-2001
			US 2001007073 A1	05-07-2001
			US 2001012938 A1	09-08-2001
			US 2001031965 A1	18-10-2001
			US 2001039452 A1	08-11-2001
			US 2001021850 A1	13-09-2001
			US 2002183746 A1	05-12-2002
			US 2002029039 A1	07-03-2002
			US 5860977 A	19-01-1999

Information on patent family members

PCT/IB2004/000390

US 5496318	A	05-03-1996	NONE
------------	---	------------	------